

# VMAX Eco-Solvent White PET Cling - Bubble Free

White PET Cling is a premium large format media with innovative cling technology for window graphics applications. It doesn't rely on adhesive, magnets or static. Very simple to attach to glass, and other smooth surfaces.

The base film of White PET Cling is made of white PET. Its low-tack and will not leave any residue on the surface.

White PET Cling is adhesive-free, smudge-free & PVC-free, 100% recyclable, and therefore environmentally friendly.

Suitable for use with:



Order Code	W (mm)	L (mm)
INV213691	1270	30

## Application instructions

1. The surfaces to cling Clear PET Cling needs to be clean and free of dirt.
2. Moisturise the glass before applying.
3. Peel the liner off gently while installing.
4. Carefully position the film so that it is properly aligned on all sides.
5. Working from middle of the graphic to all sides, continue by using a squeegee to remove air bubbles.
6. To reposition, slowly peel off the surface.

# VMAX Eco-Solvent White PET Cling - Bubble Free

## TECHNICAL SPECIFICATIONS

Properties	Result	Unit
Caliper (face)	115	micron
Weight	145	g/m <sup>2</sup>
180° Peel Strength (24Hr)	4.2g/25mm (0.15oz/in)	
Elongation	150	% max
Appearance	White Gloss	
Chemical Resistance	Resistant to most mild acids, alkalis, and salt solutions	
Service Temperature	-20° to +60°	°C
Dimensional Stability (300°F, 48Hr, Applied to a Glass)	<0.1	inch
Shelf Life (72°F, 50% R.H.)	12 months	

*NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.*