

TECHNICAL SPECIFICATIONS

VISTAFLEX® L280 LAMINATED FRONTLIT PVC BANNER 280G/M2

Features & Benefits

- Lightweight and cost effective banner
- Strong weave
- Applications: Short term indoor and outdoor banners

Printing

- The material should reach room temperature and a relative humidity of approx. 50% prior to printing.
- Ensure the material is kept free of dust, dirt and static. We recommend using gloves when handling the material.
- Conduct a print test prior to printing the material for a live project.
- Rolls up to 3.2m wide are wound Print Side Out (PSO). 3.2m rolls and above are wound Print Side In (PSI).
- Suitable for printing with Solvent, Eco-Solvent, Latex and UV-C printers.

Storage

- We recommend storing the material in its original tube and wrapping when not in use.
- Material can be stored for up to 2 years when stored in the original packaging
- Store between 20°C and 25°C at 50% relative humidity

Laminating

- This material does not require lamination. However, should the user decide to apply liquid laminate, it is their responsibility to test.



Characteristic	Result
Weight	280g/m2
Thickness	250mic ±10
Tensile Strength	
Warp	1050 N/50mm
Weft	900 N/50mm
Tear Resistance	
Warp	200 N/50mm
Weft	150 N/50mm
Temperature Resistance	-20 - +70 °C

Product Code	Width (mm)	Length (m)
ISB276073	1600	50
ISB274561	3200	100

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.