

TECHNICAL SPECIFICATIONS

VISTAFLEX® MX290 PVC MESH BANNER WITHOUT LINER 290G/M2 XT FR B1

Features & Benefits

- 290g/m2 Mesh banner without a backing liner
- Superior strength weave
- Available up to 3.2m and 5m widths
- Applications: Fence and scaffolding banners

Printing

- The material should reach room temperature and a relative humidity of approx. 50% prior to printing.
- Ensure the material is kept free of dust, dirt and static. We recommend using gloves when handling the material.
- Conduct a print test prior to printing the material for a live project.
- Rolls are wound Print Side In (PSI)
- Suitable for printing with Solvent, Eco-Solvent, Latex and UV-C printers.

- Must be printed using integrated or attachment mesh kit (ink collector)

Storage

- We recommend storing the material in its original tube and wrapping when not in use.
- Material can be stored for up to 2 years when stored in the original packaging
- Store between 20°C and 25°C at 50% relative humidity



Characteristic	Result
Total Weight	290g/m2
Thickness	330mic ±10
Tensile Strength	
Warp	2200 N/50mm
Weft	1100 N/50mm
Tear Resistance	
Warp	350 N/50mm
Weft	230 N/50mm
Air permeability Rolls 2400, 2600, 3200 (w)	1150mm/s
Air permeability *Roll 5000 (w)	810mm/s
Temperature resistance	-30°C~+70°C
Fire Certification	B1

Product Code	Width (mm)	Length (m)
ISB275558	2400	65
ISB275561	2600	65
ISB275564	3200	65
*ISB276055	5000	65

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.